



# 65TRi25MTL

## **Linear Drain**

All stainless steel drainage unit made to specified length with specified outlet position.

The 65TR25 is a standard grate design featuring a 3mm wire/5mm gap.

Manufactured from 316 marine grade the 65TR25 is 65mm wide and 25mm deep.

Please note that our TR grates have a non linished finish.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished. Electropolishing will reduce the risk of tea staining caused by the salt or chlorine.

Note: 304 grade stainless steel available on application


Refer to AS3500 for outlet pipe sizes specific to your installation.



Steel Grade 316

Code 65TRi25MTL

Range 65



Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.

#### SPECIFICATIONS + DIMENSIONS

Channel Width 72mm
Channel Depth 27mm
Length(s) As Required
Outlet Size DN40, DN50, DN65

### STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

#### **PRODUCT APPLICATIONS**

Bathroom Drainage Aged / Health Care Drainage Balcony Drainage Commercial Drainage Courtyard / Patio Drainage Driveway Drainage Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage







Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 13/09/2025 (please check for updates)