

ARCHITECTURAL

**GRATES + DRAINS** 

Code 200Custom-304-B

Category Custom Made

Recessed Channel

158mm L<u>h a a a a a a a a a a a a a a a a a a</u>

> U Channel 158mm

dimensions.

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on

Channel Material Stainless Steel

40mm Minimum

150mm Maximum

27mm Minimum

45 mm Maximum

Grate Style CR

Steel Grade 304

Range Custom Fabrication



## 200Custom-304-B **Linear Drain**

304 stainless steel 200mm wide grate and custom channel depth.

Depth between 27mm and 210mm.

Available with a 5mm wire x 5mm gap and 5mm wire x 5mm gap Grate Grip slip resistant dimple finish

Suits Load Class B.

For site specific needs or unusual situations, choose from our Custom Fabrication range.

Stormtech can customise any drainage requirements to achieve maximum efficiency

## **SPECIFICATIONS + DIMENSIONS**

**Channel Width Channel Depth** Length(s) **Outlet Size** 

210mm 27mm - 210mm As Required DN40, DN50, DN65, DN80, DN100

## STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

## **PRODUCT APPLICATIONS**

**Bathroom Drainage** Aged / Health Care Drainage **Balcony Drainage Commercial Drainage** Courtyard / Patio Drainage **Driveway Drainage** 

Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown Downloaded 13/09/2025 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.

Email info@stormtech.com.au

Phone 1300 653 403