

ARCHITECTURAL

**GRATES + DRAINS** 

Code 175Custom-316-C

Category Custom Made

Channel Material Stainless Steel

Grates longer than 1500mm supplied in sections. Tile Inserts

longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on

Grate Style CR

Steel Grade 316

dimensions

Range Custom Fabrication



## 175Custom-316-C **Linear Drain**

316 stainless steel 175mm wide grate and custom channel depth.

Available with a 5mm wire x 5mm gap and 5mm wire x 5mm gap Grate Grip slip resistant dimple finish. Depth between 27mm and 185mm.

Suits Load Class C.

For site specific needs or unusual situations, choose from our Custom Fabrication range.

Stormtech can customise any drainage requirements to achieve maximum efficiency.

## **SPECIFICATIONS + DIMENSIONS**

Channel Width **Channel Depth** Length(s) **Outlet Size** 

175mm 27mm - 185mm As Required DN40, DN50, DN65, DN80, DN100

## STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

Bathroom Drainage **Balcony Drainage Commercial Drainage** Courtyard / Patio Drainage Driveway Drainage Pool and Spa Area Drainage

Suspended Slab Drainage Wet Area Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown Downloaded 13/09/2025 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.

**PRODUCT APPLICATIONS** 



Paved Area Drainage Shower Drainage Special Needs Drainage Threshold Drainage